Charging Options

INTEGRUS Digital Infrared Products

www.ListenTech.com



Specify Part Number LBB 4560/00

Integrus 56-Unit Charging Suitcase

This sturdy, hard side case can store and charge up to 56 Integrus Pocket Receivers. Suitcase has a convenient removable lid. Has rapid charging capability so units can charge in under 2 hours. A universal mains power facility enables charging around the world. Also has a charging status indicator for each unit.

Benefits

- Can accommodate 56 receivers
- Charging Suitcase has a removeable lid
- Universal mains power facility allows use worldwide
- Rapid recharging: maximum time required; 1 hour and 45 minutes
- Mains cable included





Integrus 56-Unit Charging Cabinet

This sturdy, hard side case can store and charge up to 56 Integrus Pocket Receivers. Has rapid charging capability so units can Specify Part Number LBB 4560/50

charge in under 2 hours. A universal mains power facility enables charging around the world. Also has a charging status indicator for each unit.



Listen Technologies Corporation 8535 South 700 West, Suite A Sandy, UT 84070-2515 U.S.A. Phone: 1.801.233.8992 or 1.800.330.0891 Fax: 1.801.233.8995 Email: info@ListenTech.com

Don't miss a single sound.



Charging Options

www.ListenTech.com

Digital Infrared Products

Specifications

opeemeanons			
Physical	Mounting Dimensions H x W x D	n/a	screws and plugs for wall mounting
		9 x 27 x 21 in. (230 x 690 x 530 mm)	5 x 27 x 20 in. (130 x 680 x 520 mm)
	Weight excl. receivers	34 lbs. (15.5 kg)	25 lbs. (11.2 kg)
	Weight incl. 56 receivers Finish	49 lbs. (22.3 kg) Charcoal with grey	40 lbs. (18.0 kg)
		0 /	
Electrical and Optical Characteristics	Mains voltage	90 to 260 V, 50 to 60 Hz	
	Power consumption	270 W (56 receivers charging)	
	Power consumption (standby)	17 W (no receivers in the charging unit)	
System Environmental Conditions	Working conditions	Fixed/stationary/transportable	
	Temperature range - transport	-40 to 158 °F (-40 to + 70 °C)	
	Temperature range - operating	41 to 113 °F (+5 to + 45 °C)	
	Maximum relative humidity	< 93%	
	Safety	According to EN 60065, CAN/CSA-E65 (Canada and US) and UL 6500	
	EMC emission	According to harmonized standard EN 55103-1 and FCC rules part 15, complying with the limits for a class A digital devices	
	EMC immunity	According to harmonized standard EN 55103-2	
	EMC approvals	Affixed with the CE mark	
	ESD	According to harmonized standard EN 55103-2	
	Mains harmonics	According to harmonized standard EN 55103-1	
	Environmental requirements	Contains no banned substances as specified in UAT-0480/100 (e.g. no cadmium or asbestos)	

Photographs, CAD drawings, etc. available at www.ListenTech.com.

Warranty

Most Bosch equipment carries a 3 year limited manufacturer's warranty (excluding accessories) to be free from defects in workmanship and material under normal use and conditions. Bosch rechargeable batteries carry a 1 year warranty. All Bosch accessory items carry a 90-day warranty to be free from defects in workmanship and material under normal use and conditions. Warranty does not cover normal wear and tear on the product or any other physical damage unless the damage was the result of a manufacturing defect. This warranty is void if damage occurred because of misuse or if the product has been repaired or modified by anyone other than a factory authorized service center. Contact Listen or see the Listen website for further details.

Accessories



LBB 4550/00 Integrus Receiver Rechargeable NiMH Battery Pack NiMH battery pack to be used with LBB 4550 Integrus Pocket Receiver. Features a temperature sensor for an optimal charging process. Battery life is up to 75 hours.

Don't miss a single sound.